**decorgraff**

## 65402 — Enviro Wall Linen

65402 Enviro Wall Linen is vinyl wall paper for the use of all solvent, eco-solvent, UV and latex printers. Its texture design and tear resistance lends style and grace to any interior space and a truly elegant choice that is superb for decorating the commercial, residential and public places requiring a sophisticated look and feel. Its fine texture produces sharp imagery and brings out lusciously rich tonal qualities to dress a space to perfection.

Self -adhesive or pre-paste is recommended for easy application and it saves time to prepare a standalone adhesive required for traditional wall covering,even you can decorate it at home by yourself. Save labor hour, time and money.

## Media Attributes

| | |
|---|---|
| **Texture:** | Linen |
| **Material:** | 125gsm ± 5% vinyl on the surface<br>120gsm ± 5% pulp paper on the back. |
| **Basis Caliper:** | 14.2mil ±1 mil |
| **Basis Weight:** | 245gsm ± 5% |
| **Whiteness :** | 78.2% |
| **Available Width:** | 42" (1.07M); 54"(1.37M)   **Length:** 50M |
| **Life expectancy:** | 10 years as long as the room humidity being kept under 90% & no moisture come out from wall &away from direct sun |
| **Optimum printing Environment:** | 70° F (30-70% Relative Humidity) |
| **Storage recommendation:** | 5~30 Celsius degree |

## Application Guidelines

| | |
|---|---|
| **Printing:** | The print side is wound to the outside of the roll. |
| **Printer Setting:** | To optimize print quality, printers should be set for "Enhanced Multi-pass" print quality mode. |
| **Printer and Ink Compatibility:** | The material can be printed with any solvent, ecosolvent, UV & Latex printers. |

SOLVENT   ECO SOLVENT   LATEX   UVC

**MS MULTISYSTEM TECHNOLOGY(FZE)**
Step ahead

W/H: Q4-110
P.O.Box: 121710
Sharjah Airport International Free Zone
United Arab Emirates

Phone : +971 6 557 99 29
Fax : +971 6 557 99 28
E-mail : multisys@eim.ae
Web : www.multisys.me